

Shenzhen Southern Machinery Sales and Service Co., Ltd

Add:Room 1806 Block 3 Jinyun COFCO, Qianjin 2nd Road, Xixiang, Baoan District, Shenzhen, China

Automatic Solder Robot





- 1, The use of temperature control, capable of soldering at lower temperatures, so your PCB board or the parts will not be damaged because the temperature is too high.
- 2, Due to lower soldering temperatures, can increase the life of the tip.
- 3, The machine's System allows the tip of the set temperature remains stable, not because heat is sucked part or PCB board need to wait for the tip back to temperature, when the automatic operation is not because of this phenomenon resulting in poor quality of welding.




4, The temperature drop is small, 0.1 seconds back to the temperature (temperature difference within 10 degrees), the temperature error of \pm 1 $^{\circ}$ C.



Model	S- A300 Three Axis Solder Robot S- B400 Thour Axis Solder Robo			
Number of axis	3		4	
Effective distance	X-axis	300mm	X-axis	300mm
	Y-axis	300mm	Y-axis	300mm
	Z-axis	100mm	Z-axis	100mm
	\	\	R-axis	±360°
Maximum Speed	X-axis	500mm/s	X-axis	500mm/s
	Y-axis	500mm/s	Y-axis	500mm/s
	Z-axis	300mm/s	Z-axis	300mm/s
	\	/	R-axis	300dg/s
Repeatability	X-axis	±0.02mm	X-axis	±0.02mm
	Y-axis	±0.02mm	Y-axis	±0.02mm
	Z-axis	±0.02mm	Z-axis	±0.02mm
	\	\	R-axis	±0.02°
Load	Y-axis	10.0Kg	Y-axis	10.0Kg
	Y-axis	5.0Kg	Y-axis	5.0Kg
Teaching format	Teaching pendanl			
Range of tempreature	±5.0°C			
Dimension	650mm*600mm*720mm			
Power source	AC220V50/60HZ			
Air	Dry air4 ~ 5kgf/cm²			



Customizable online welding:





Range of application



digital frequency display



LED welding



usb welding



CFL welding



Welcome inquiry

- 1,Please visit: www.smthelp.com
- 2, Find us more: https://www.facebook.com/autoinserter
- 3, Know more our team: https://cn.linkedin.com/in/smtmachine
- 4, Welcome to our factory in Shenzhen China
- 5, Google: Auto+Insertion
- 6, Looking forward to your email: angela_kuo@126.com