

S-PM750V Epoxy Resin Mixer

Epoxy Resin Mixer Serial

Description

Suitable for mixing Epoxy Resin, also other materials, such as LED photoelectric, Siler paste, Nano powder material and so on

Features

- 1. Rotation/revolution with a high power vacuum pump
- 2. Can mixing high-viscosity material using 2 centrifugal force: rotation and revolution in a short time
- 3. Large capacity: Maximum 1500ml (2*750ml)
- 4. Up to 11 preset programs (Can be customized), suitable for different types materials
- 5. Max rotation speed up to 2000rpm
- 6. Time control setting: Accurate to 1s
- 7. Convenient running: Touch screen & obvious button
- 8. Highly stability in use





www.smthelp.com



Specifications

Model	S-PM750V	Weight	120KG
Machine Size(L*W*H)	681*686*740mm	Spindle Cooling Mode	Normal Air-cooled(can choose Oil-cooled: Continuous operation for more than 30 minutes or high-speed rotation in a single instance)
Mixing Capacity	750ml/jar, 2 jars/time		
Mixing Method	Centrifugal mixing + Vacuum		
Mixing Angle	45°		
Power	1.2KW		
Applicable temperature, humidity, and voltage	10-45°C, 20-80%RH, Ac220V 50/60HZ	Safety Protection Device	Cannot start operation when the upper cover is not closed, emergency stop, motor overload alarm, automatic stop when a fault occurs
Running Speed	200-2000rpm		
Vacuum Pump	Oil-free Vacuum Pump (can choose external oil-sealed)		
Vacuum Degree	35mba(6mba)~1atm, accuracy 0.01KPa	Program Storage Capacity	11
Vacuum Flow Rate	100L/Min*2	Setting Time	1-999s(Totally 5 steps), Accurate to 1s
Control Mode	Variable Frequency Drive Control, Touch Screen Preset, Human-machine	Transmission Ratio & Mode	Mechanically constant(Optional rotation and revolution, separately adjustable from 10-100%). Gear Transmission
	Interface		www.smthelp.com



SOUTHERN MACHINERY S-PM750V Epoxy Resin Mixer Epoxy Resin Mixer Serial

Epoxy Resin Mixer Serial

Material Mixer Video & Pictures





www.smthelp.com



S-PM750V Epoxy Resin Mixer

Epoxy Resin Mixer Serial

7 Benefits for Choosing S-PM750V

- 1. High running speed (up to 2000rpm): bubble removal quickly
- 2. Lower noise
- 3. Better stability
- 4. Clearly Buttons for control
- 5. High sealing performance
- 6. Durable bearing: smooth rotation
- 7. High durability: use famous brand motor





Best After-sales service

- Free Installation/ Training
- 1 day lead-time (spare parts)
- 5 days customized design
- 7x24 Worldwide Support



Welcome Inquiry

Please visit

www.smthelp.com

Find us more

https://www.facebook.com/autoinsertion

Know more our team

https://www.linkedin.com/company/smtmachine

Welcome to our factory in Shenzhen China

See more our machine please Google

Auto Insertion

Youtube

https://www.youtube.com/c/Smthelping

Looking forward to your email

info@smthelp.com