

S-2000 Jumper Wire Auto Insertion Machine



Specifications

1	speed	22000 CPH
2	Non-performing rate	Less than 500 PPM
3	Insert direction	Parallel 0° , 90° , 180° , 270°
4	Components span	5.0mm-20mm
5	PCB Size	(Min)50 MM * 50MM、(Max)450 MM * 450MM
6	PCB thickness	0.79-2.36mm
7	components :Jumper (JW)	0.5mm-0.7mm in diameter copper tin
9	Components Length	1.2-2.2MM (adjustable)
10	Components Arc	10-35° (adjustable)
11	Machine Size (L × W ×H) /Weight	1800mm×1600mm×1800mm /1000kg
13	Power supply	220V, AC (single phase) 50/60 HZ, 1.5KVA;
14	System Protection	UPS, power can run 15 minutes
15	Working Power	1200W (Energy-saving)
16	Air pressure /Air consumption	0.5 Mpa / 0.2 m ³ /m
20	Coordinate correction	Machine vision systems, multi-point MARK vision correction.
21	driving system	AC Servo、 AC motors
22	Data input method	USB interface input (EXCEL document format),
24	Workstations running way	Clockwise and anti-clockwise
25	PCB transfer mode	Manual



www.smthelp.com