

Manual assembly line



Item	Name	Specifications(L*W*H)	Amount
A	Iron material Assembly line	10000*400* (750) 1900 (mm)	1line
—	Device	(Overall lacquer that bake - computer white)	
1	Nose Power	Chassis iron material, built-in (200 w) and one produces the forever of horizontal machine adjustable electronic governor 3 to 10 m/min, 160 steel roller diameter, diameter of 32 adjusting 1 roller, chain, bearing, etc	1set
2	Lighting	28WT5energy saveing light. Each lamp is equipped with independent switch;	14sets
3	Process	Bilateral configuration, "H" type	20Sets

	board	aluminum, up and down a A4 hard plastic sleeve per meter;	
4	Machine body	Stent use 38 * 38 * 1.0 (mm) iron box section production, support and guide using 50 * 50 * 1.2 (mm) iron box section production, machine screws adjustable feet \pm 50 mm	
5	Belt	Width 400mm,Thickness 2mm, adopt green anti-static conveyor belt (seamless interface)	
6	Retainer	Using \varnothing 25 mm galvanized bearing roller, on condition of span is 300 mm chooses 2 m \varnothing 25 mm galvanized bearing roller span;	
7	Instrument desk	Width 400mm , board with 15 mm, semicircle wood package edge;	10m
8	Worktable	Size 300mm board adopt 15mm high quality plywood, Anti-static rubber surface green, semicircle wood package edge;	20m
7	Power	40*60Galvanized trough match with Richard card three 3 multi-function socket and 2.5 square line, install the bracket in the middle;	12m
8	Electricity box	General electric box/set of built-in switch electronic products, etc;	1set
9	Other	All supporting tube adopts 20 * 40 (mm) machine is made of iron	
10	Noted		