

Lead-Free Reflow Oven S-6600-PC



• FEATURES

- ○ Complete for the lead free process
- ○ Adopt instrument control System and closed loop control for heating source of each zone.
- ○ Temperature control adopt circulation hot air heating mode for each zone;
- ○ Closed loop control for conveyor system, can go along steadily stepless rate-adjusting;
- ○ With over heating alarm function;

Heating Zones :Top 6/Bottom 6
Heating length :2300mm
Cooling zone :2
Max.width of PCB :350mm
Conveyordirection:L→R (R→L.option)
Height of conveyor :Mesh belt 880±20mm
Transport system :Mesh belt
Conveyor speed :0-2000mm/min
Power supply : 5 Wire 3 phase 380V 50/60HZ
Power of start up :24KW
Power of consumption of operation :Approx.3-5 KW
Control fashion :PC
Warm-up time :About 20 minutes
Rangeoftemperaturecontrol:RoomTemperature-350℃
Temperature control :Industrial temperature control module to control the SSR drive
Precisionoftemperaturecontrol:±1℃
Temperatureredistributingerror:±3℃
Trouble alarm: Temperature anomaly(Ultra high temperature or ultralow temperature after constant temperature)
Weight :Approx.450kg
Dimension(mm): L3600×W700×H1430

Welcome inquiry

1, Please visit : www.smthelp.com

2, Find us more: <https://www.facebook.com/autoinsertion>

3, Know more our team: <https://cn.linkedin.com/in/smtsupplier>

4, Welcome to our factory in Shenzhen China

5, Google: Auto+Insertion