

Shenzhen Southern Machinery Sales and Service Co., Ltd

Add:Room 1806 Block 3 Jinyun COFCO, Qianjin 2nd Road , Xixiang, Baoan District, Shenzhen ,China

1. Pick& Place machine without own recycling waste of material function?
2. SMT workshop of material, not easy to collect?
3. Frequently stuck phenomenon often happen?
4. Production site clean and tidy, cause losing customer orders?

SCRAP TAPE CUTTER

*The machine for SMT tape cutting equipment, used in SMT machine of material recycling, own recycled drawer, convenient for workers centralized processing

*Completely replace personnel manual tape cutting, and implements the function of tape and film can be one size fits all;

*Better to demonstrate good 5 s management ability .



Characteristic

Applicable to all kinds of SMT material, from 0.04 mm film to 1.5 mm thick tape can be easily cut
Machine dimensions:(L)900X(W)260X(H)430, cover an small area (shape size is customized by feeder head width)

Flexible cutting : only 26 kg weight, equipped with four straight caster, convenient transportation

Antistatic type, material box + stainless steel stent borders, is equipped with safety sensors

State police, no material box without shear zone

Precision CNC machining cut lead drive system + double linear guide

Adopt CNC sheet metal process + high adhesion pensu processing, durable, high atmosphere.

Precision gear motor drive, no need of compressed air, reduce the unstable blanking of pressure fluctuations.

New features:

S - 680A intelligent automatic cutting machine:

New features: material box of sensor increase to 2 or more

Join the buzzer alarm

Card is timeout alarm and motor protection

Increase the manual recovery door (other waste put hole)

Advanced imported cutter, soft belt cutting ability




Technical parameters:

Model	S - 680A
Use temperature and humidity	10±40 degrees ,20%-90%RH temperature
Tape material	8 m of tape 8-44 m plastic tape Ethylene soft belt cutting (optional)
Blanking cycle	9 seconds (excluding delay pauses)
Effective blanking width	680 mm (can be made according to customer's machine)
Dimension	(L)900X(W)260X(H)430
Weight	26 kg
Power	0.05 KW
The main consumption cycle	The butcher (import high speed steel) consumption cycle: 1-2 years Deputy knife (import high speed steel) consumption cycle: 1-2 years Drive belt consumption cycles: 1-2 years

Comparison



Use before



After use

Contact:

Chan :

Skype :chan12477357

Email :chan@smthelp.com

Q Q :2355736092

Phone :+86 15012477357

Website:www.smthelp.com

*Facebook : Search “Auto Insertion”

Southern
Machinery