

SME-5200 Fixture Cleaning Machine is used to clean grease, flux, dusts on the surface of all kinds of SMT fixtures, tray, reflow oven cooler and filter, wave-soldering oven claw, chains, and nets...etc.

SME-5200 is made up of wash unit, rinse unit, dry unit, rotation cleaning basket unit and control unit. Put the dirt SMT fixtures on to the cleaning basket, setting the cleaning parameters, the machine will automatically complete wash, rinse and dry process by just pushing start key. The fixtures after cleaning is very clean and dry, ready to use at any time.



SME—Professional Cleaning Equipments Supplier for SMT & PCB





Fixture cleaning

Reflow oven/Wave oven fixture, plate

**Composite stone, Steel,
Aluminum materials**



**Reflow oven/Wave oven
maintenance**

Cooler, filter, chains...


**Any machine parts with
flux on them**




Parts cleaning


Grease,oil on plastic, hardware,
electrical-parts

**Any parts which can be
cleaned**



Advantages





- Total SUS 304 structure, resist Acid and Alkali corrosion, firm and attractive.
- 1 meter diameter big cleaning round basket, can clean 20~40 pcs fixtures at one time.
- Clean liquid spray from 3 spray rods on upper/lower and front side, cleaning basket rotates during cleaning.
- Clean liquid pressure up to 6kg/cm², make it thoroughly clean of whole fixture.
- PLC program control, Touch-panel operation, cleaning parameters can be set and change conveniently.
- Easy One-button operation, high pressure clean+ rinse+ hot air dry, all process complete in a cycle automatically.
- Clean liquid and water heat and temperature keeping function.
- Closed-loop clean and rinse, clean detergent and rinse water are cycling filtered and reused in the machine.
- Standard equipped solution and water auto fill in and discharge function.
- The fixtures are clean and dry after cleaning, standby and ready for use at any time.


Item	SME-5200 Spec
Cleaning basket size	Φ1000mm x H 200mm. Special size option
Spray unit	Upper/lower/front side,720° all-around spray
3-level filter system	1mm /50um/20um filters
Clean tank capacity	80L
Rinse tank capacity	80L
Clean spray pressure	5~6 kg/cm ²
Clean time	5~15 Min
Rinse time	1~3 Min
Dry time	10~20Min
Clean detergent heat temp	Room temp~80°C
Rinse water heat temp	Room temp~80°C
Hot air heat temp	Room temp~90°C
Clean pump power	2.2KW
Clean detergent power	9KW
Hot air heat power	9KW
Air blower power	4.0KW
Air supply	0.5~0.7Mpa
Power supply	3 P,AC 380V,50/60HZ,33KW
Machine size	L1380 x W2100 x H 1400 (mm)
Machine weight	500KG

1.Cleaning Basket



- A. 1m diameter round cleaning basket, batch clean fixture, basket turns during clean, rinse and dry process.
- B. clean-rinse- dry , the total process time is 30~40min

2. Pumps and air blower



A.High quality, big flow cleaning pumps。


B. High flow rate blower, reduce hot air dry time 。

3.Liquid tank/water tank/SUS304pipes/auto liquid/water fill in and drain out function







- A. Total SUS304 machine。
- B. Auto liquid/water fill in and drain out function.
- C. Liquid tank and water tank and separated pipe system

4.Control System



- A. Famous electric devices: Mitsubishi PLC, Touch panel, Inventor, Schneider Contactor, Relay, CKD solenoid valve, OMRON power unit.
B. Isolated and protected power supply and distribution system





Welcome inquiry

1, Please visit : www.smthelp.com

2, Find us more: <https://www.facebook.com/autoinsertion>

3, Know more our team: <https://cn.linkedin.com/in/smtsupplier>

4, Welcome to our factory in Shenzhen China

5, Google: Auto+Insertion

6, See machine working video: youtube - Auto Insertion

7, Looking forward to your email: jasonwu@smthelp.com